



General Product Specifications

Sewoo 3" Printers: LK-P30



Printing Method	Direct thermal
Printing Speed	100mm/sec
Printing Width	72mm
Resolution and Pitch	203 DPI, PITCH : 8 Dot/mm, 0.125 Pitch
Barcodes Printed	1D: EAN-8, EAN-13, Code39, ITF, UPC-A, UPC-E, Codabar, Code93, Code128 2D: PDF417, QR Code, Maxicode
Paper Width	25.4 - 80mm
Roll diameter	Max. Ø 56mm (core roll inner diameter 8.5mm ± 0.5mm)
Connectivity	Standard USB Serial RS232C
Internal Memory	SDRAM: 16MB FLASH: 32MB
Sensors	Paper end Gap Black mark Cover open
Reliability	TPH life: 50km Pulse activation: 50,000,000 pulse or more (12.5% Print Ratio)
Emulation	ESC/POS, CPCL, ZPL Command compatible
Operating Environment	Operating temperature: -10 - 50°C (14 - 122°F) Operating humidity: 10 ~ 90%
Storage Environment	Storage temperature: -20 - 60°C (-4 - 140°F) Storage humidity: 10 ~ 90%
Drop Resistance	1.8m (6ft) onto concrete
IP Rating	IP42, IP54 (with case)
Dimensions	W x D x H(mm): 100×158×85 W x D x H(inch): 3.93×6.22×3.34
Weight	615g (with battery)
Certifications	KCC, CE, FCC, UL/cUL
Battery	7.4V / 2200mAh, 2600mAh Li-ion, 3.3 Hrs Charging Time, 100 Hrs Stand-by. External Charger (Output 8.4VDC/0.8A)

www.stimare.net

www.lineapro.store

info@stimare.net

info@lineapro.store

USA +1-720-257-7070

UK +44-208-0998071

Ireland +353-1-6854600

We are the experts in:

BARCODE SCANNING

MOBILE PRINTING

POINT-OF-SALE (POS)