




## T10 Rewinder

### The Rewinder Everyone Can Use

The T10 rewriter has an idler arm that can be positioned to rewind labels from either side of the printer.

Depending on the user's requirements, the T10 can rewind "inside or outside" label rolls.



Modular core adaptor fits 1", 1.5" & 3" core sizes



Colored LED indicator provides rewriter operation status



Rewinding direction switch to rewind "inside or outside" label rolls



Stylish appearance plus a rugged design for long term reliability

Model		T10 Rewinder
Paper width		4.72" (Max.)
Rewind Speed		12 IPS
Label Roll		8" (Max.)
Core Roll		Coreless, 1" (25.2~25.6 mm), 1.5" (40~40.6 mm), 3" (76~76.6 mm)
Label Roll Weight		5 Kg
Rewinding		Label Inside / Outside
Switches		Rewind
Motor		Hybrid Motor
Power		100~240 VAC 24W, 24V Adapter
Environment	Operating Temp.	41°F to 104°F (5°C to 40°C)
	Storage Temp.	-4°F to 140°F (-20°C to 60°C)
Humidity		10-85% (non-condensing RH)
Size (H*W*D)		303 mm * 180 mm * 349 mm
Agency Approvals		CE, FCC Class A
Weight		5 Kg (11 lbs)
Warranty		2 years

\* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.