

# A8 Compact. Reliable. Flexible.



## Features

- 3" Jam-Free Direct Thermal POS Printer
- Compact Cube Design for Limited Counter Space
- Paper Top Exit and Front Exit for Flexible Operation
- Fast Printing Speed of up to 250mm/s
- High Resolution of up to 203dpi
- USB+Serial+Ethernet Interface
- Optional Bluetooth & WiFi Interfaces for Mobile Devices
- mPOS friendly Compatible with Android and iOS




## Specifications

Print	<b>Print Method</b>	Direct Thermal
	<b>Print Speed</b>	250mm/s
	<b>Print Resolution</b>	203.2 dpi (8dots/mm)
	<b>Print Width</b>	72mm
Print Font	<b>Character Size</b>	Font A 13 x 26 dots, Font B 10 x 20 dots, Extra Font A 12 x 24 dots
	<b>Character per Line</b>	Font A 42, Font B 56, Extra Font A 48
	<b>Character Sets</b>	Alphanumeric: 95 Extended Graphics: 128 x 37 Page International: 32 Unicode: UTF-8
	<b>Barcode Types</b>	1D : Coda Bar, Code39, Code93, Code128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D : PDF417, QR Code
	<b>Graphics</b>	Supporting User-Defined Fonts, Graphics, Logos
Media	<b>Type</b>	Thermal Roll Paper
	<b>Paper Feed</b>	Friction Feed
	<b>Loading</b>	Drop In
	<b>Width</b>	58mm, 80mm
	<b>Roll Diameter</b>	Max. 83mm
	<b>Thickness</b>	70µm
	<b>Auto Cutter</b>	Full or Partial Selectable
	<b>Partition</b>	2 inch (58mm) (Option)
Reliability	<b>MCBF</b>	60million Lines
	<b>TPH</b>	150km
	<b>Auto Cutter</b>	1.5million Cuts
General	<b>Interface</b>	Prime Model : Serial + USB + Ethernet + (Option : WiFi/Bluetooth) Standard Model : Serial + USB + (Option : WiFi/Bluetooth)
	<b>Support Mobile Operating Systems</b>	Android, iOS (SDK)
	<b>Receive Buffer</b>	4kb
	<b>Printer Driver</b>	Windows / OPOS / JPOS Driver, Linux CUPS Driver, Virtual COM USB Driver, Utility Program
	<b>Utility</b>	NV
	<b>Sensors</b>	Paper End, Cover Open
	<b>Drawer</b>	2 Port (via Y-Type Adaptor)
	<b>Power Supply</b>	24V, 2A
	<b>Temperature &amp; Humidity</b>	Operating : 0 ~ 45°C, 10 ~ 80% RH (No condensations) Storage : -20 ~ 60°C, 10 ~ 90% RH (No condensations)
	<b>Safety Standards</b>	CE, FCC
	<b>Dimensions (W x H x D)</b>	130 x 129 x 130.2 (mm), 5.1 x 5.07 x 5.1 (in)
	<b>Packing Dimensions(W x H x D)</b>	260 x 290 x 205 (mm), 10.23 x 11.41 x 8.07 (in)
	<b>Weight</b>	Prime Model : 752g, 1.65lbs / Standard Model : 746g, 1.64lbs
	<b>Packing Weight</b>	Prime Model : 2.45kg, 5.40lbs, Standard Model : 2.44kg, 5.37lbs
	<b>Color</b>	Dark Grey, White
	<b>Options</b>	Bluetooth, WiFi
	<b>Eco</b>	RoHS
<b>Warranty</b>	3 Years (Max.)	
<b>What's in the Box</b>	A8, Power Supply(Adapter, Power Cord), Paper Roll(30Ø), Installation Guide, USB Cable, Serial Cable (Option)	


\* Specifications may change without prior notice.

## Dimensions

Unit : mm



## I/O Interfaces



- ① Drawer Kick-Out
- ② Power Connector / 24V
- ③ Serial
- ④ Ethernet
- ⑤ USB (B type)

## Ordering Information

Part No.	Description
A8 P(B)	Direct Thermal POS Printer USB+Serial+Ethernet Interface, Dark Grey
A8 P(W)	Direct Thermal POS Printer USB+Serial+Ethernet Interface, White
A8 PW(B)	Direct Thermal POS Printer USB+Serial+Ethernet Interface, Dark Grey WiFi/Bluetooth Option
A8 PW(W)	Direct Thermal POS Printer USB+Serial+Ethernet Interface, White WiFi/Bluetooth Option

